


SOLAR CONTROLLER **MEC48100LN**

◆ DESCRIPTION:

A Multitask Electronics solar controller is a small box consisting of solid state circuitry that is placed between a solar panel and a battery. Its function is to regulate the amount of charge coming from the panel that flows into the deep cycle battery bank in order to avoid the batteries being overcharged. A controller can also provide a direct connection to appliances, while continuing to recharge the battery.




◆ FEATURES:

- **PWM Charging:** high charge efficiency and greatly extends the battery life.
- **MOSFET as Electronic Switch:** makes the controller a longer life.
- **Protection Functions:** makes the system be more secure and reliable, includes overcharge protection, deep discharge protection, reverse polarity protection of module/battery/load, short circuit protection of module/load, open circuit protection without battery, over-temperature protection, battery overvoltage shutdown.
- **LCD Display:** real-time shows the system status of charging, discharging and fault.
- **Sufficient Design Margin:** maximum capacity exceeds 20% as the rated current/power, which makes the system more secure.
- **Intelligent Cooling Fans:** it is controlled by the real-time heat sink's temperature, which makes the fan a longer life and saving energy.
- **Metal Case:** after spray treatment, the controller is more beautiful and durable.

 3 years  RoHS CE

◆ APPEARANCE:





**MULTITASK
ELECTRONICS:RS:**

	Model	MEC48100LN
System Specifications	Rated Voltage	48V
	Rated Current	100A
	Float Voltage	55.2V
	Idle Draw	≤70mA
Input	Max Current On Charging	100A
	Max Open Voltage	100V
Output	Max Load Current	/
Protection Function	Over charge	58.4V±0.2V
	Over discharge Protection(V)	43.2V±0.2V
	Over discharge Resumption(V)	49.6V±0.2V
	Over-voltage Protection(V)	68V
	Over-voltage	60V
	Reverse Polarity	Yes
	Short Circuit	Yes
Other Data	Working Temperature	-20~70°C
	Storage Temperature	-35~80°C
	Temperature Compensation	-4mV/2V/°C
	Display	LCD
	Operating Altitude(m)	≤5000m
	Product Size	350mm×300mm×180mm
	Packing Size	354mm×304mm×183mm
	Product Weight	6400g
Packing Weight	6600g	

◆ **INSTALLATION DIAGRAM:**

